


- 氣吸式起子依據SKD-BN500L系列加裝氣吸頭改裝而成，主要應用在吸取無磁性螺絲，如塑膠螺絲/鋁製螺絲/不銹鋼螺絲...無法帶磁性螺絲等。
- 使用時只需更換KS-58吸取頭即可，使用方便，不同尺寸螺絲只需更換氣吸取頭即可，更換簡單，使用方便。
- 氣吸式專用泵浦體積小，可適用任何氣吸式起子。
- 氣吸式泵浦吸力強搭配螺絲盤使用更加方便與順手，使用者可先將螺絲放置螺絲盤上，再使用氣吸式起子吸取螺絲。

技術參數		SKD-VBN512L	SKD-VBN512P	SKD-VBN519L/P	SKD-VBN517L/PF	SKD-VBN512L/P	SKD-VBN512P/PF
輸入電壓		DC24V or DC32V					
扭力	(kgf.cm)	1.5-12	2-12	3-19	3-17	1.5-12	2-12
	(Lbf.in)	1.33-10.44	1.77-10.44	2.57-16.45	2.57-14.78	1.32-10.44	1.74-10.44
	(N.m)	0.15-1.18	0.2-1.18	0.29-1.96	0.29-1.67	0.15-1.18	0.2-1.18
扭力精度(%)		±3%					
扭力調整		無段式					
空轉速	Hi	1000	1000	1000	2000	2000	2000
	LO	700	700	700	-	-	-
適用螺絲	機械牙	1.6-3.0	1.6-3.0	2.3-3.5	1.6-3.0	1.6-3.0	1.6-3.0
直徑(mm)	自攻牙	1.6-2.6	1.6-2.6	2.3-3.0	1.6-2.6	1.6-2.6	1.6-2.6
額定功率		55W					
重量(g)		520					
長度(mm)		283					
ESD(Anti-Static)		✓ (金屬外殼)					
CE認證		✓					
CCC認證		✓					
RoHS		✓					
適用電源控制器		SKP-32BC-60W			SKP-BE32HL(GP)		
適用起子頭		C 			D 		

外部尺寸



吸頭規格

PART NO	d1	d2	D	H	Bl Dia (mm)	T x D x L
P11032	2.2	3	4	1.3	00X1.5X60	
P11032-1	2.7	4	5	1.5	0X2.0X60	
P11032-2	3.2	4.5	5.5	2	1X2.5X60	
P11032-3	3.7	5.8	6.8	3	SH200-1X3 (Dx60) SH200-2X3 (Dx60)	

